



TECHNICAL SPECIFICATIONS

IKAWA SAMPLE ROASTER FOR PROFESSIONALS

Model	GO50
Mains Supply	100V, 110-130V or 220-240V as required
Power	1.35kw, 1.4kw, 1.5kw max (respective of above mains supply)
Capacity	60g(2.1 oz) green coffee
Dimensions	240 x 130 x 320mm (12 x 5
Weight	4.12kg (9lbs)
Design Features	Temperature Sensors - PT1000 Grade A Temperature Control - Proportional, Integral, Differential, Predictive-Jayaram (PID-J) Integrated cyclone for chaff collection and consistent air flow PID-controlled fan
Safety Certifications	Conforms with IEC-60335-1 and IEC-60335-2-9, UL and other international standards
Includes	1x IKAWA Sample Roaster, 1x Collection Jar, 1x Power Lead, 1x Cardboard Packaging, access to IKAWA profile library

IKAWA PRO APP

App	Free to download from Apple App Store and Google Play Store
System	iOS and Android
Connection	Bluetooth 4.0
Roast Points	Up to 20 temperature points on each sensor line and 10 airflow points
Roast Time	0-20 minutes: sample roasts typically takes 5-10 minutes
During Roast	Real Time Temperature display from 1 sensor Colour change, 1st Crack Edit Roast Profiles during roast Customs cooling parameters
During Roast	Save Roast, Add Notes, Data, Photos Data Export to CSV Share by Email, Text, Social Media